



WATERBASED EXTERIOR CLEAR STAIN BASE  
SERIES TEX-000  
STAIN BASE

**DESCRIPTION:**

Wiping waterbased clear stain base. Can be used on many wood species that are used in furniture, moldings and exterior doors. It can be used alone or with exterior wb systems. This product is very easy to wipe off and has a good transparency. It is easy to apply and gives low grain raising finish.

**PRODUCT DATA:**

PRODUCT CODE: TEX-000  
VISCOSITY (25°C): 30 à 60 sec (FC#4)  
SOLID % by Vol: 8%  
SOLID % by WT: 8%  
VOC: 542 g/L  
DENSITY: 1.02 g/L  
SHELF LIFE: 12 months

**APPLICATION:**

*Surfaces should be clean, dry and free from grease and oil. Mix well before using. Sand with paper #180 - #220, minimum.*

**APPLICATION EQUIPMENT:**

CONVENTIONNAL  
AIRLESS/AIR ASSIST  
BRUSH/ROLER/RAGS

**MIXING RATIO:**

COLORATION: 40% maximum  
COLORANTS: 85T41, 85T42, 89TXX

**DRYING TIMES:**

(after wiping)  
TOUCH DRY 1 hour  
TIME BEFORE WIPING: 1-4 minutes  
READY TO RECOAT: 1-2 hours  
COMPLETE DRYING: 14-16 hours

**STORAGE:**

To be kept in a dry place at a temperature never under 5°C. After use, cover lids tightly.

**Note:** Drying times may vary depending on thickness applied, temperature and/or humidity.

**Warning:** Clean equipment with water. Use corrosion resistant equipment. Do not use the same equipment for solvent based products.

The customer is responsible for following the recommended application procedures. Failure to adhere to these specifications may result in poor appearance or failure of film. This product is for professional use only. Consult your local representative before applying with other manufacturer products. The customer should test the complete system for adhesion, compatibility and performance prior to full scale application. Please refer to the Safety Data Sheet (SDS) for safety information and precautions prior to using this product. We ONLY guarantee our product to conform to our quality. Our responsibility as manufacturer is limited to the cost of the product. Please feel free to contact us at (819) 367-2201 for any further inquiries regarding this product. All information on this product data sheet is subject to change without notice.